

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **Thermometer liquid**  
 SDS-Ref 061315, 061316, 079070, 0759001TS

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use

#### 1.3 Details of the supplier of the safety data sheet

Steinbach International GmbH  
 L. Steinbach Platz 1  
 4311 Schwertberg  
 Austria  
 Telephone: +43 7262 61431 1000  
 e-Mail: info@steinbach-group.com  
 e-Mail (competent person): sdb@steinbach-group.com

#### 1.4 Emergency telephone number

Country	Name	Postal code/city	Telephone	Opening hours
Austria	Vergiftungsinformationszentrale	1090 Wien	+43 1 406 4343 (24h)	
United Kingdom	National Poisons Information Service		111 (24h)	

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.6	flammable liquid	3	Flam. Liq. 3	H226
3.10	aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

#### 2.2 Label elements

Labelling

- Signal word

Danger

- Pictograms

GHS02, GHS08



- Hazard statements

H226

Flammable liquid and vapour.

H304

May be fatal if swallowed and enters airways.

- Precautionary statements

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P301+P310

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303+P361+P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P331

Do NOT induce vomiting.

## Thermometer liquid

Version number: GHS 6.3 (2023-03-21)

Replaces version: GHS 5 (2023-02-06)

- Precautionary statements
  - P405 Store locked up.
  - P501 Dispose of contents/container to hazardous or special waste collection point.
- Hazardous ingredients for labelling
  - Kerosine (petroleum)

### 2.3 Other hazards

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of  $\geq 0,1\%$ .

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0,1\%$ .




## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture).

### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Classification acc. to GHS	Pictograms	Wt%
Kerosine (petroleum)	CAS No 8008-20-6  EC No 232-366-4  Index No 649-404-00-4	Flam. Liq. 3 / H226 Asp. Tox. 1 / H304	 	$\geq 90$
1-(2-methyl-4-(2-methyl-phenylazo)phenylazo)-2-naphthol	CAS No 85-83-6  EC No 201-635-8	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319		< 2.5

For full text of abbreviations: see SECTION 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Take off immediately all contaminated clothing. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Self-protection of the first aider.

Following inhalation

Mouth to mouth resuscitation should be avoided. Use alternative methods, preferably with oxygen or compressed air driven apparatus. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Rinse mouth with water (only if the person is conscious). Let be drunken in little sips: 0,1-0,2l Water. Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

### 4.3 Indication of any immediate medical attention and special treatment needed

None.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media

Water jet

### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Ventilate affected area.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: Kieselgur (diatomite), Sand, Universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use only in well-ventilated areas. Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

#### Control of effects

- Protect against external exposure, such as

High temperatures, Frost, UV-radiation/sunlight

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

#### Packaging compatibilities

Professional use: Only packagings which are approved (e.g. acc. to ADR) may be used. Consumer use (private households): Keep only in original container.

#### Conditions of storage

Keep container tightly closed in a cool place. Protect from sunlight. Keep away from children.

### 7.3 Specific end use(s)

There is no additional information.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
GB	hydrocarbon mixture (RCP method)		WEL		1,100		2,200				EH40 / 2005
GB	cycloalkanes (>C7)	8008-20-6	WEL		800						EH40 / 2005

## Thermometer liquid

Version number: GHS 6.3 (2023-03-21)

Replaces version: GHS 5 (2023-02-06)

### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
GB	cycloalkanes (C5-C6)	8008-20-6	WEL		1,800						EH40 / 2005

#### Notation

Ceiling-C	ceiling value is a limit value above which exposure should not occur
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

### Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Kerosine (petroleum)	8008-20-6	DNEL	18.75 mg/kg bw/day	human, oral	consumer (private households)	chronic - systemic effects

## 8.2 Exposure controls (professional use)

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

- Eye/face protection

Use safety goggle with side protection (EN 166).

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Type of material

PVC: polyvinyl chloride, NR: natural rubber, latex

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection

In case of inadequate ventilation wear respiratory protection: Full face mask (DIN EN 136).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

## Thermometer liquid

Version number: GHS 6.3 (2023-03-21)

Replaces version: GHS 5 (2023-02-06)

Physical state	liquid
Colour	red
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	≥146 °C at 101.3 kPa
Flammability	not relevant (fluid)
Lower and upper explosion limit	not determined
Flash point	40 – 60 °C
Auto-ignition temperature	220 °C (auto-ignition temperature (liquids and gases))
pH (value)	not determined
Kinematic viscosity	not determined
Particle characteristics	no data available
Oxidising properties	none
Vapour pressure	
Vapour pressure	≤3.7 kPa at 37.8 °C
Density and/or relative density	
Density	not determined
Relative vapour density	information on this property is not available
Other safety parameters	
Solubility(ies)	not determined
Partition coefficient	
n-Octanol/water (log KOW)	this information is not available

## 9.2 Other information

Information with regard to physical hazard classes

there is no additional information

Other safety characteristics

there is no additional information

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s).  
Risk of ignition.

If heated:

Risk of ignition

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

## 10.5 Incompatible materials

Oxidisers

## 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to GHS

##### Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful in contact with skin.

Name of substance	CAS No	Exposure route	End-point	Value	Species
Kerosine (petroleum)	8008-20-6	oral	LD50	>5,000 mg/kg	rat
Kerosine (petroleum)	8008-20-6	dermal	LD50	>2,000 mg/kg	rabbit
1-(2-methyl-4-(2-methyl-phenylazo)phenylazo)-2-naphthol	85-83-6	oral	LD50	3,600 mg/kg	rat

##### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

##### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

##### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

##### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

##### Carcinogenicity

Shall not be classified as carcinogenic.

##### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

##### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

##### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

##### Aspiration hazard

May be fatal if swallowed and enters airways.

### 11.2 Information on other hazards

There is no additional information.

## SECTION 12: Ecological information

### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of  $\geq 0,1\%$ .

### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0,1\%$ .

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Other disposal recommendations

Dispose of contents/container to hazardous or special waste collection point. Waste treatment of containers/packagings: Mixed municipal waste.

### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.




### SECTION 14: Transport information

<b>14.1 UN number or ID number</b>	1223
ADR/RID/ADN	UN 1223
IMDG-Code	UN 1223
ICAO-TI	UN 1223
<b>14.2 UN proper shipping name</b>	KEROSENE
ADR/RID/ADN	KEROSENE
IMDG-Code	KEROSENE
ICAO-TI	Kerosene
<b>14.3 Transport hazard class(es)</b>	
ADR/RID/ADN	3
IMDG-Code	3
ICAO-TI	3
<b>14.4 Packing group</b>	III (substance presenting low danger)
ADR/RID/ADN	III
IMDG-Code	III
ICAO-TI	III
<b>14.5 Environmental hazards</b>	non-environmentally hazardous acc. to the dangerous goods regulations
<b>14.6 Special precautions for user</b>	
Provisions for dangerous goods (ADR) should be complied within the premises.	
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	
The cargo is not intended to be carried in bulk.	


### Information for each of the UN Model Regulations

#### Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

Classification code	F1
Danger label(s)	3
	
Special provisions (SP)	664
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3
Tunnel restriction code (TRC)	D/E
Hazard identification No	30
Emergency Action Code	3Y

#### Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) -

##### Additional information

Classification code	F1
Danger label(s)	3
	
Special provisions (SP)	664
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3

## Thermometer liquid

Version number: GHS 6.3 (2023-03-21)

Replaces version: GHS 5 (2023-02-06)

Hazard identification No 30  
**International Maritime Dangerous Goods Code (IMDG) - Additional information**

Marine pollutant -  
 Danger label(s) 3



Excepted quantities (EQ) E1  
 Limited quantities (LQ) 5 L  
 EmS F-E, S-E  
 Stowage category A

**International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information**

Danger label(s) 3



Excepted quantities (EQ) E1  
 Limited quantities (LQ) 10 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

##### Seveso Directive

No	Dangerous substance/hazard categories
P5c	flammable liquids (cat. 2, 3)

##### Deco-Paint Directive

VOC content	100 %
-------------	-------

##### Industrial Emissions Directive (IED)

VOC content	99 %
-------------	------

#### Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

None of the ingredients are listed.

#### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

None of the ingredients are listed.

#### Water Framework Directive (WFD)

None of the ingredients are listed.

#### Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

#### National inventories

Country	Inventory	Status
EU	REACH Reg.	all ingredients are listed

#### Legend

REACH Reg. REACH registered substances

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.1	SDS-Ref: 061315, 061316, 0759001TS	SDS-Ref: 061315, 061316, 079070, 0759001TS	yes

#### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ADR/RID/ADN	Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN)
Asp. Tox.	aspiration hazard
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits ( <a href="http://www.nationalarchives.gov.uk/doc/open-government-licence/">http://www.nationalarchives.gov.uk/doc/open-government-licence/</a> )
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	seriously damaging to the eye
Eye Irrit.	irritant to the eye
Flam. Liq.	flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	the Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
ppm	parts per million
RCP	reciprocal calculation procedure
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	corrosive to skin
Skin Irrit.	irritant to skin
STEL	short-term exposure limit
TWA	time-weighted average
VOC	Volatile Organic Compounds
vPvB	very Persistent and very Bioaccumulative
WEL	workplace exposure limit

#### Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

#### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

## Thermometer liquid

Version number: GHS 6.3 (2023-03-21)

Replaces version: GHS 5 (2023-02-06)

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.